



LINERS TO MEET THE DEMAND FOR EVERY APPLICATION

Hammerhead Trenchless carries eight types of liners for CIPP applications to best meet customer needs, unique projects and curing methods. Our Liners are constructed of the highest quality for reliable and consistent installation. Our liner and resin systems are compliant with industry installation standards including ASTM F1216 – *Standard practice for rehabilitation of existing pipelines and conduits by the inversion and curing of resin-impregnated tube*, Uniform Plumbing Code (UPC), International Plumbing Code (IPC), NSF International (NSF14), IAPMO, and ICC-ES.

HH LED LINER

Proprietary synthetic polyester fiber liner with polyurethane coating designed specifically for use with the BlueLight curing system. Used in applications 4 – 10 inches in diameter with single bends up to 45°.

HH LED 3D LINER

Proprietary synthetic polyester fiber liner with polyurethane coating designed specifically for use with the BlueLight curing system. This 4-inch liner is a preferred choice for installations with single or multiple bends up to 90° and/or where the host pipe configuration includes a single diameter transition (4 – 6").

HH FLEX LED LINER

Proprietary synthetic polyester fiber liner with polyurethane coating designed specifically for use with the BlueLight curing system. Used in applications from 3 to 4 inches in diameter to minimize wrinkling and installs through single or multiple bends up to 90° and/or where the host pipe configuration includes single diameter transitions (3 – 4" and 4 – 6").

HH SCRIM LINER

Designed for accuracy, scrim reinforced liner minimizes longitudinal stretch and assures accurate inversion length. This polyester needle-punched felt liner with reinforcing polyester scrim and polyurethane coating is used in applications where the host pipe is 3 to 12-inch diameter with bends at a maximum of 45°. Ambient or heat cure using hot water circulation is recommended.

CURING METHOD



BLUELIGHT



BLUELIGHT



BLUELIGHT



AMBIENT



HOT WATER

IT'S ALL HERE

HH TRANSITIONAL SCRIM LINER

Polyester needled felt liner with reinforcing scrim and polyurethane coating custom manufactured for host pipes with diameter transitions. Ambient or heat cure using hot water circulation is recommended.

HH FLEX LINER

Flexible polyester needle-punched felt liner with polyurethane coating and sewn seam used in applications where the host pipe is 4 to 8-inch diameter with bends of 45 and 90°. Ambient or heat cure using hot water circulation is recommended.

WOVO/BRAWOLINER

Highly flexible, premium, woven, seamless PET premium liner with polyurethane coating used in applications from 2 to 8-inch diameter to minimize wrinkling and install through single or multiple bends up to 90°. Ambient or heat cure using hot water circulation is recommended.

WOVO/BRAWOLINER 3D

Premium, woven, seamless PET premium liner with polyurethane coating used in applications to minimize wrinkling and install through single or multiple bends up to 90° and/or where the host pipe configuration includes diameter transitions. Ambient or heat cure using hot water circulation is recommended. Available in 3 to 4, 4 to 6 and 6 to 9-inch transitions.

CURING METHOD



AMBIENT



HOT WATER



AMBIENT



HOT WATER



AMBIENT



HOT WATER



AMBIENT



HOT WATER

Liner	Diameter								Bends		Pre-Wetout Liner	Transitions*	Cure Method
	2"	3"	4"	5"	6"	8"	10"	12"	45°	90°			
LED Liner			X	X	X	X	X		X		X		BlueLight
LED 3D Liner			X	X	X				X	X	X	X	BlueLight
FLEX LED Liner		X	X						X	X	X	X	BlueLight
HH Scrim Liner		X	X	X	X	X	X	X	X				Ambient, Hot Water
Transitional Scrim Liner			X		X							X	Ambient, Hot Water
Flex Liner			X	X	X	X			X	X		X	Ambient, Hot Water
Wovo/Brawoliner	X	X	X	X	X	X			X	X			Ambient, Hot Water
Wovo/Brawoliner 3D		X	X	X	X	X			X	X		X	Ambient, Hot Water

*Single diameter transitions.



REHAB & REPLACEMENT. **REDEFINED**

Learn more: hammerheadtrenchless.com