



HIGH TECH, HIGH PERFORMANCE CABLE WINCH

HYDROGUIDE® HG550

»»» INFINITELY ADJUSTABLE

Allows pulling speed and tonnage to be precisely matched to each unique job's requirements

»»» RAPID PULLBACK AND PAYOUT

Gets the job done up to 20% faster than competing units

»»» DATA TRACKING

Records performance data for accurate documentation, job assessment or reporting



»»» ENHANCED SAFETY

Only HammerHead Trenchless offers an Electrical Strike Indicator Device (ESID) option for added safety near utilities

BECAUSE NO TWO JOBS ARE ALIKE.

Whether you're slitting gas line or pulling in product, the materials you work with vary. The length and lay of runs vary. Customer requirements vary. The HG550 gives you infinite proportional control of up to 5.5 tons of pulling force with line payout and pullback speeds up to 20 percent faster than competing winches. Now you can match any job's unique requirements. And while any operator can say they did the job well, the HydroGuide HG550 erases any doubt. The unit's data tracking system records performance information you can use for your own documentation, for training, or for your project reports. With the HG550, the data speaks for itself. And if your jobs have you working near electrical utilities, HammerHead Trenchless is the only winch manufacturer to offer an optional Electrical Strike Indicator Device (ESID) for added safety.



PROPORTIONAL POWER-TO-SPEED. The HG550 winch gives you infinitely variable control over 5.5 maximum tons of force and payout/pullback speeds from 3 inches to 110 feet per minute – ideal for slitting plastic gas pipes ½ inch to 2 inches in diameter, pulling back product or cleaning sewer pipe.

DATA-BASED PRODUCTIVITY. The easy-to-read Precision Digital Job Data Recorder keeps track of line speed, distance, force and pressure. Plug in a USB flash drive to download data, or plug in the optional printer for hardcopy right on-site.

SIGNATURE SUPPORT. You need more than just a manufacturer for your trenchless operations – you need a partner. At HammerHead® Trenchless, it is our mission is to help you succeed on every job. Our customer service is available 24/7, so you always get your answers when you need them. Our world-class, on-site training keeps your crews confident and efficient. And when your job calls for a custom solution, our team of industry experts is ready to help. At HammerHead Trenchless, the most important feature on all of our products is the signature support that comes with it.

EQUIPMENT SPECIFICATIONS

HYDROGUIDE® HG550	Rig size L/W/H – in (m)*	122/69.5/51 (3.1/1.8/1.3)
	Weight – lb (kg)**	2,500 (1,134)
	Max. pulling force – tons (t)	5.50 (5.0)
	Engine – HP (kw)	21.5 (16) @ 3,000 RPM
	Engine manufacturer/model	Kubota® D902, diesel
	Cooling system	Liquid cooled
	Max. pressure – psi (bar)	3,050 (210)
	Max. payout speed – fpm (mpm)	110 (33.5)
	Max. pullback speed – fpm (mpm)	80 (24.4)
	Max. usable cable capacity – ft (m)***	3,000 (914.4)
	Usable downrigger length – ft (m)	5 (1.5) or 10 (3.05)
	Swaged cable diameter – in (mm)	0.394 (10)
	Weight per foot – lb (kg)	0.37 (0.17)
	Braking system	Wheeled unit – Standard, electric Track unit – Standard, hydraulic

FEATURES	Multi position leveling jacks	Wheeled unit – (1 front, 2 rear) Skid mount unit – (2 front, 2 rear) Tracked unit – (2 rear)
	Electric start	Standard, 12VDC
	Capstan control	Fully proportional directional valve
	Capstan drive motor system	Single, dual speed radial piston
	Job data recorder	Onboard, digital control/display
	Light package	Wheeled unit – (Trailer, down-hole) Skid mount unit – (Down-hole) Tracked unit – (Down-hole)
OPTIONS	Job data printer	Portable, thermal strip, via USB
	Most extensions – ft (m)	5 (1.50) or 10 (3.05)
	Electrical strike identification (ESID)	Yes
	All-terrain track mount (AT)	Yes

*Without optional accessories. **Weight does not include cable or optional accessories. ***Maximum capacity of 3,050 (929.6).

CALL 800.331.6653
FOR A FREE PROJECT CONSULTATION TODAY.

HAMMERHEADTRENCHLESS.COM
800.331.6653 (USA ONLY) | INTERNATIONAL: +1 920.648.4848

